

Lamato CF SERIES

Flat bed 3 Needle Interlock Stitch Machine

Yamato's CF series strongly help you to win success from the most crucial competition at quality, cost, and delivery.







Flat bed 3 Needle Interlock Stitch Machine

Nnmbering on Model:

CF2303M-156M/FC

① Symbol of Series ② Class No. ③ Number of Needle: 3 = 2, 3 needle ④ Submodel by Application

(5) Top Cover Thread Mechanism : 1 = with Top Cover Thread Mechanism

Specification

| Model | Application | ļ | Ф | <u></u> | <u>*</u> | ₹ <u>*</u> ‡ | 4.0 4.0 | 1-1 | ţĬ | (1) is |
|---------|---------------------------------|-------------------|-------|---------------------------------|-----------|--------------|--------------------------|-----|----|--------|
| CF2300M | For Decorative Seam etc. | UY128GAS 3 (2) | 5 (4) | 4.8 5.6 6.4 | 1.4 - 3.6 | | | 6 | 31 | 5500 |
| CF2303M | For Binding BSb-1/605 | UY129GAS 3 (2) | 5 (4) | 3.2 4.0 4.8 5.6 6.4 | 1.4 - 3.6 | * | 1:0.7-1:2 ∞} ÷ | 5 | 31 | 5500 |
| CF2339M | For Attaching Lace LSa-1/605 | UY129GAS 3 (2) | 5 (4) | 4.0 4.8 5.6 | 1.4 - 3.6 | | | 4 | 31 | 5000 |

TEL:+86-574-86800518.86800558/FAX:+86-574-86800555/E-mail:marketing@yamato-china.com

YAMATO SEWING MACHINE MFG, CO., LTD. (HEAD OFFICE) TEL: #81-6-6384-5821/FAX: #86-6-6384-7185/E-mail export-dept@yamato-sewing.com

YAMATO U.S.A. INC. TEL:+1-803-548-0334/FAX:+1-803-548-0405

YAMATO EUROPE GmbH. TEL:+49-40-355347-0/FAX:+49-40-354371/E-mail:sales@yamato.de

YAMATO (HONG KONG) CO., LTD. TEL:+852-2721-0251/FAX:+852-2723-0444/E-mail:yamato@yamato-sewing.com.hk

雅満棟(香港)有限公司 东莞代表处 TEL:+86-769-86231363/FAX:+86-769-86231362 大和體訊机制造株式会社 青岛事务所 TEL:+86-532-85783175/FAX:+86-532-85783172 TEL:+88-21-64400017;64400019/FAX:+88-21-64400021

VAMATO SINGAPORE PTE LTD. TEL:+65-6287-1955/FAX:+65-6287-1028/E-mail:sales@yamato-sewing.com.sg

YAMATO SINGAPORE PTE LTD, INDIA LIAISON OFFICE, TIRUPUR MAIN BRANCH TEL:+91-421-4333701/FAX:+91-421-4333702/E-mail:yamato-sewing@airteibroadband.in

YAMATO SINGAPORE PTE LTD, INDIA LIAISON OFFICE, DELHI BRANCH TEL:++91-11-41603280/FAX:+91-11-40574681 YAMATO SINGAPORE PTE LTD, CUSTOMER SERVICE CORRESPONDENT IN JAKARTA, INDONESIA FAX: +62-21-781-8727

YAMATO SINGAPORE PTE LTD., BANGLADESH LIAISON OFFICE TEL: +88-02-899-1884/FAX: +88-02-899-1885

YAMATO MEXICO OFFICE TEL:+52-55-5784-9090/FAX:+52-55-5578-1470

THE RESIDENT REPRESENTATIVE OFFICE OF YAMATO SEWING MACHINE MFG. CO., LTD IN HO CHI MINH CITY TEL: +84-8-6296067/FAX: +84-8-38113384

Yamato's CF series strongly help you to win success from the most crucial competition at quality, cost, and delivery.

Offering ideal seam.

Keeping out the small dust.

Yamato's seam is high in elasticity and strong in durability. The oil can stay clean with a filter, which is easy to replace. You can enjoy high quality finish.

There is no problem in sewing with synthetic fiber thread.

HR Device (Silicone supplying unit for needle point)and SP Device (Silicone supplying unit for needle thread) to avoid thread breakage and skip stitch are equipped as standard.





Easy threading.

Threading for looper thread can be easily done by swinging up thread take-up eyelet.





Pushbutton stitch length regulator.

Stitch length is freely adjustable with pushbutton system. The pushbutton can also be locked to prevent the set stitch length from being changed against your will.








Easy way to prevent skip stitching.


Fine adjustment of Looper locus according to needle size can be done easily.



Solving oil leakage.

New oil seal prevents oil from leaking at needle bar area.





Differential ratio according to materials can be adjusted by pushing a lever up and down. Differential lever can be adjusted even while the machine is running.

The lever is completely covered at the time of sewing so that smooth flow of fabric is obtained.



Ready-to use package and easy handling(CF2300M).

In addition to newly designed covers with which operators can set their hands closer to needle dropping point, user friendly fabric guides are included for good quality finish in hemming and covering.

