

ADJUSTING STITCH LENGTH BY PUSHING BUTTON

Stitch length is simply and quickly adjustable by a pushbutton system.




LEVER-ADJUSTABLE DIFFERENTIAL FEED

The differential ratio is simply adjusted by the Differential Feed Control Lever. Differential ratio can be adjusted according to the material. The adjustment can be done even during the sewing.



EASY-THREADING AND TROUBLE FREE FOR THREAD WINDING AROUND THREAD TAKE-UP CAM

Threading for looper can be done easily by sewing up type thread take-up eyelet. The special blush prevents the thread from winding around LooperThread Take-up Cam.



PREVENT SKIPPING STITCH

Locus and avoiding motion of looper can be adjusted for different sewing conditions.



ELIMINATING DUST

Oil filter device can keep the lubricate oil clean and easy to change.



STABLE PERFORMANCE AT HIGH SPEED

The fan inside the pulley of VF blows wind to the oil base to cool the oil temperature when the machine is running at high speed.



EASY SEWING WITH SYNTHETIC FIBER THREAD


To avoid thread breakage, skip stitch and needle hole, the HR device (cooling unit for needle point) and the SP device (silicone supplying unit for needle thread) are equipped as standard.



IDEAL SEWING PERFORMANCE

Perfect sewing performance with the looper thread mechanism and top cover thread mechanism. VF series can meet wide variety of sewing condition. They are fit for both light and heavy materials.

2,3 NEEDLE HIGH SPEED FLAT BED INTERLOCK STITCH MACHINE



2,3 NEEDLE HIGH SPEED FLAT BED INTERLOCK STITCH MACHINE

Numbering on Model

VF2403-148M-21/EC



- ① Symbol of Series
- ② Class No.
- ③ Number of Needle : 4 = 2 Needle 5 = 3 Needle
- ④ Sub-model
- ⑤ Additional Features
No Mention = Standard
P = With Puller (tooth puller, rubber puller)
S = Stepping Motor Driven Elastic Metering Device (Swing-out type)
- ⑥ Top Cover Thread Mechanism
0 = Without top cover thread mechanism
1 = With top cover thread mechanism
- ⑦ Needle Distance :
32 = 3.2mm 40 = 4.0mm 48 = 4.8mm
56 = 5.6mm 64 = 6.4mm
- ⑧ Shape of Stitch Tongue on Stitch Plate
M = for medium heavy material
L = for light material
S = special
- ⑨ Special Specification
- ⑩ Device(s)

Devices

- UT: Solenoid type under thread trimmer
- UT-A: Air type under thread trimmer
- ST2: Solenoid type top cover thread trimmer
- ST2-A: Air type type top thread trimmer
- K1: Automatic thread chain cutter (horizontal type)
- FC: Tape cutter (Manual type)
- EC: Solenoid type tape cutter
- EU5: Solenoid type fully automatic type cutter at the beginning and end of seaming
- EU20: Same as above, multi programmable type
- AU2: Air type fully automatic type cutter at the beginning and end of seaming
- AU20: Same as above, multi programmable type
- S: Fixed type elastic tape inserter
- S1: Flexible type Elastic tape inserter

		Under thread trimmer	Wiper	Foot lifter	Foot lifter + wiper	Upper thread trimmer	Remarks
Air type	UT-A32	●	—	—	●	—	Wiper and foot lifter works at the same time
	UT-A34	●	●	●	—	—	Wiper and foot lifter works independently
	UT-A34/ST2-A	●	—	●	—	●	
Solenoid type	UT-2	●	●	●	—	—	
	UT-4	●	—	●	—	—	
	UT-4/ST2	●	—	●	—	●	

Specification and appearance on this catalogue are subject to change without notice. For correct handling of products described on this catalogue, please read instructions carefully before operation.

YAMATO SEWING MACHINE MFG. CO., LTD.
<http://www.yamato-sewing.com>

HEAD OFFICE
 4-12, 4-CHOME, NISHI-TENMA, KITA-KU, OSAKA, 530-0047, JAPAN
 TEL:+81-8-6364-5621 / FAX:+81-8-6364-7185 / E-mail: export-dept@yamato-sewing.com

YAMATO U.S.A. INC. TEL:+1-803-548-0334/FAX:+1-803-548-0405
 YAMATO EUROPE GmbH. TEL:+49-40-355347-0/FAX:+49-40-354371/E-mail:sales@yamato.de
 YAMATO (HONG KONG) CO., LTD. TEL:+852-2721-0251/FAX:+852-2723-0444/E-mail:yamato@yamato-sewing.com.hk
 雅美特(香港)有限公司 香港代表处 TEL:+86-769-86231363/FAX:+86-769-86231362
 大和縫紉機(寧波)有限公司 TEL:+86-574-86800518/86800558/FAX:+86-574-86800555/E-mail:marketing@yamato-china.com
 大和縫紉機製造株式会社 青島事務所 TEL:+86-532-85783175/FAX:+86-532-85783172
 大和縫紉機製造株式会社 上海事務所 TEL:+86-21-64400017,64400019/FAX:+86-21-64400021
 YAMATO SINGAPORE PTE LTD. TEL:+65-6287-1955/FAX:+65-6287-1028/E-mail:sales@yamato-sewing.com.sg
 YAMATO SINGAPORE PTE LTD, INDIA LIAISON OFFICE, TIRUPUR MAIN BRANCH TEL:+91-421-4333701/FAX:+91-421-4333702/E-mail:yamato-sewing@airtelbroadband.in
 YAMATO SINGAPORE PTE LTD, INDIA LIAISON OFFICE, DELHI BRANCH TEL:+91-11-41603280/FAX:+91-11-41603281
 YAMATO SINGAPORE PTE LTD, CUSTOMER SERVICE CORRESPONDENT IN JAKARTA, INDONESIA Fax: +62-21-781-8727
 YAMATO MEXICO OFFICE TEL:+52-55-5764-9090/FAX:+52-55-5578-1470
 THE RESIDENT REPRESENTATIVE OFFICE OF YAMATO SEWING MACHINE MFG. CO., LTD IN HO CHI MINH CITY TEL:+84-8-62969057/FAX:+84-8-38113384



Yamato's "Made in Japan" VF series, which keep contributing to global garment industry with its sewing performance, enable you to have more stable & high product quality and highly efficient production.

Now, Yamato's VF series adopt new technology! Presenting you highly efficient production.

'Non-stain' minimizes oil stains on your products




~ YAMATO "Non - stain" technology ~

Special seal, which prevents oil from leaking at needle bar area, is used to avoid oil stains on materials. (PAT.P)



● Saving - "Non - stain" increases productivity

"Non - stain" finish minimizes your loss, such as downtime and extra cost caused by spot removing operation.



● good performance and long life - durable machines

Yamato "Non - stain" technology will not sacrifice performance and durability of machines, but keep the machine running smoothly at high speed for long life.



Yamato's flat bed interlock stitch machine improves the efficiency and realizes the beautiful and stable sewing finish.



Please choose the most suitable model for your application from our wide variety of submodels.



● VF2400, VF2500

2,3 NEEDLE FLAT BED INTERLOCK STITCH MACHINE

Basic model of VF series. For general hemming, covering and decorative seaming.



● VF2403, VF2503

2,3 NEEDLE FLAT BED INTERLOCK STITCH MACHINE FOR BINDING

Guide can be set up near the needle dropping place and help you obtain neat finish even if sewing the small corner.



● VF2429-8, VF2529-8

2 NEEDLE FLAT BED INTERLOCK STITCH MACHINE FOR ATTACHING LACE

It is equipped with stepping motor driven elastic metering device and right hand fabric trimmer. You can get expected tension when attaching lace. Moreover, it enables you to get perfect sewing finish when sewing thin material.



● VF2560

4 NEEDLE FLAT BED INTERLOCK STITCH MACHINE

It is suitable for 4 needle decorative seaming and general seaming.



● VF2510

3 NEEDLE FLAT BED DOUBLE CHAIN STITCH MACHINE WITH SPREADER THREAD FOR ATTACHING THE FACING TO POCKETS ON SLACKS IN ONE OPERATION

VF2510 covers the edge of the facing with spreader thread and attaches the facing in one operation. Therefore, it can eliminate the serging operation.



MODEL	SEAM	APPLICATION	UY128GAS	4	3.2	1.4 - 3.6	10.7 - 12	6~8	31	6500
For General Interlock Stitch										
VF2400		2 needle flat bed interlock stitch machine	UY128GAS 2	4 (3)	3.2 4.0 4.8 6.4	1.4 - 3.6	10.7 - 12	6~8	31	6500
VF2500		3 needle flat bed interlock stitch machine	UY128GAS 3	5 (4)	4.8 5.6 6.4	1.4 - 3.6		6~8	31	6500
VF2500-PA3		3 needle interlock stitch machine for patch work sewing and decorative stitching	UY128GAS 3	5 (6)	5.6	1.4 - 2.0		7	31	6000
VF2560		4 needle flat bed interlock stitch machine	UY118GKS 4	6	5.6 6.4	1.4 - 3.6		4.5	26	5500
For tape binding (elastic tape binding)										
VF2403		2 needle flat bed interlock stitch machine for binding	UY128GAS 2	4 (3)	3.2 4.0 4.8 6.4	1.4 - 3.6	10.7 - 12	6~8	31	6500
VF2404		2 needle interlock stitch machine for binding, with mechanical metering device for inserting elastic tape	UY128GAS 2	4 (3)	3.2 4.0 4.8	1.4 - 3.6		5	31	5000
VF2503		3 needle flat bed interlock stitch machine for binding	UY128GAS 3	5 (4)	4.8 5.6 6.4	1.4 - 3.6		6~8	31	6500
VF2504		3 needle interlock stitch machine for binding, with mechanical metering device for inserting elastic tape	UY128GAS 3	5 (4)	5.6	1.4 - 4.2		7	33	5000
For attaching lace, elastic tape										
VF2429-8		2 needle, with right hand fabric trimmer and stepping motor driven elastic metering device	UY128GAS 2	4 (3)	3.2 4.0	1.4 - 3.6	10.7 - 12	6~8	31	5000
VF2439-1-8		2 needle, with right hand fabric trimmer and mechanical metering device	UY128GAS 2	4 (3)	3.2 4.0 4.8	1.4 - 3.6		4 (8)	31	5000
VF2529-8		3 needle, with right hand fabric trimmer and stepping motor driven elastic metering device	UY128GAS 3(2)	5 (4)	6.4	1.4 - 3.6		6~8	31	5000
VF2539-1-8		3 needle, with right hand fabric trimmer and mechanical metering device	UY128GAS 3(2)	5 (4)	5.6	1.4 - 4.2		7	33	5000
VF2459-8		Lip binding use, with right hand fabric trimmer and stepping motor driven elastic metering device	UY128GAS 2	4	3.2	1.4 - 3.6		5	31	5000
Double chain stitch machine										
VF2402		2 needle double chain stitch machine needle distance: 4.8, 6.4, 8.0, 9.5mm	UY128GAS 2	4	4.8 6.4 8.0 9.5	1.4 - 3.6	10.7 - 12	8	31	6000
VF2408		1 needle double chain stitch machine	UY128GAS 1	2	4.8 5.6 6.4	1.4 - 4.2		7	33	6500
VF2502P		3 needle double chain stitch machine for overlocking Jeans, with puller	UY128GAS 3	6	6.4	1.4 - 3.6		8	31	5000
VF2510		3 needle double chain stitch machine with spreader thread for attaching the facing to pockets on slacks in one operation	UY128GAS 3	5 (7)	8.8 (2.4+6.4)	1.4 - 3.6		4.5	31	5000

● Optional special presserfoot, stitch plate, guide for attaching wide lace, elastic tape are available.